## In the Claims:

## Claims 1-13 (canceled):

Claim 14 (new): A circuit arrangement comprising:

an active EMI filter including an input and an output, said input connected to receive an output voltage from a power switching stage and said output of said active EMI filter providing a filtered output voltage to a load;

a current sensor sensing a common mode current to said load;

an amplifier stage including first and second transistors each controlled by said current sensor, collectors of said first and second transistors sharing a common connection;

isolating circuitry coupled to said common connection and a ground line, wherein said isolating circuitry passes a current to cancel said common mode current in said ground line.

Claim 15 (new): The circuit arrangement of claim 14, wherein said first and second transistors are complementary.

Claim 16 (new): The circuit arrangement of claim 14, wherein said current sensor comprises a current transformer including first and second primary windings and first and

Page 3 of 9

second secondary windings, said first and second secondary windings being connected to additively reflect said common mode current in said first and second secondary windings.

Claim 17 (new): The circuit arrangement of claim 14, wherein said current sensor comprises a current transformer including first and second primary windings and first and second secondary windings, said first and said second primary windings coupled respectively to input terminals of said active EMI filter and said first and second secondary windings coupled respectively to said first and second transistors.

Claim 18 (new): The circuit arrangement of claim 17, wherein said first and second transistors are complementary, only one of said complementary transistors conducting depending upon a direction of a current in said first and second secondary windings.

Claim 19 (new): The circuit arrangement of claim 16, wherein one of said first and second transistors is turned ON to allow said reflected common mode current to flow through said isolating circuitry to cancel ground noise current flowing in said ground line, thereby canceling said ground noise current flowing back to said input.

Claim 20 (new): The circuit arrangement of claim 14, wherein said power switching stage comprises an output stage including an inductor and a capacitor, said

Page 4 of 9

output voltage provided across said capacitor.

Claim 21 (new): The circuit arrangement of claim 14, wherein said power switching stage comprises a switch mode power supply.

Claim 22 (new): The circuit arrangement of claim 14, wherein said ground line connects said load and said power switching stage.

Claim 23 (new): The circuit arrangement of claim 14, wherein said output voltage of said power switching stage comprises direct current.

Claim 24 (new): The circuit arrangement of claim 14, wherein said output voltage of said power switching stage comprises alternating current.

Claim 25 (new): A circuit arrangement comprising:

an active EMI filter including first and second input terminals and first and second output terminals and a ground return line connected to a ground return line terminal;

said input terminals of said active EMI filter connected to receive an output voltage of a power transistor switching stage and said output terminals of said active EMI filter providing a filtered output voltage;

wherein said active EMI filter comprises a current transformer including first and

Page 5 of 9

second primary windings and first and second secondary windings, said first and second secondary windings being connected to additively reflect said common mode current in said first and second secondary windings;

wherein said active EMI filter cancels said common mode current that flows between said input terminals and said output terminals.

Claim 26 (new): The circuit arrangement of claim 25, wherein said power transistor switching stage comprises an output stage including an inductor and a capacitor, said output voltage provided across said capacitor.

Claim 27 (new): The circuit arrangement of claim 25, said active EMI filter comprising an amplifier stage including first and second transistors each controlled by said current transformer, said first and second transistors sharing a common connection, said common connection coupled to isolating circuitry and said ground line, said isolating circuitry passing a current to cancel said common mode current in said ground line.

Claim 28 (new): The circuit arrangement of claim 27, wherein said first and second transistors are complementary.

Claim 29 (new): The circuit arrangement of claim 25, wherein said power transistor switching stage comprises a switch mode power supply.

Page 6 of 9

Claim 30 (new): The circuit arrangement of claim 25, wherein said active EMI filter comprises complementary transistors, only one of said complementary transistors conducting depending upon a direction of a current in said first and second secondary windings.

Claim 31 (new): The circuit arrangement of claim 24, wherein said ground line connects said load and said power transistor switching stage.

Claim 32 (new): The circuit arrangement of claim 25, wherein said output voltage of said power transistor switching stage comprises direct current.

Claim 33 (new): The circuit arrangement of claim 25, wherein said output voltage of said power transistor switching stage comprises alternating current.